

Figure Funnei DEF20CFF4

Gross Power 39.8 kW (53.3 hp / 54.1 ps) @ 2,400 rpm

Net Power 36.8 kW (49.3 hp /50 ps) @ 2,400 rpm

Breakout Force 20.4 kN

Rated Operating Capacity 795 kg

Bucket Capacity 0.4 m³

Operating Weight 3,120 kg

365B SKID STEER LOADER

365B SPECIFICATIONS >>>

ENGINE	
Emission Regulation	Stage V
Make	Yunnei
Model	DEF20CFF4
Gross Power	39.8 kW (53.3 hp / 54.1 ps) @ 2,400 rpm
Net Power	36.8 kW (49.3 hp / 50 ps) @ 2,400 rpm
Peak Torque	200 N · m @ 1,800 rpm
Number of Cylinders	4
Displacement	2.0 L
Cooling Type	Water

2 V
0 amps
۰

CHAIN TANK

Drive Chain Size	80 HS	
TIRES		
Ply Type	Pneumatic	
Tire Size	10-16.5	
Ply Rating	12	

HYDRAULIC SYSTEM	
System Type	open
Standard Flow	76.8 L/min
Traveling Hydrostatic Pressure	35 MPa
Working Hydrostatic Pressure	21 MPa
Hydraulic Cycle Time, total	7.7 s
Raise	3.8 s
Dump	1.8 s
Lower (float down)	2.1 s

OPERATING WEIGHT	
Operating Weight	3,120 kg

PERFORMANCE	
Static Tipping Load	1,590 kg
Rated Operating Capacity	795 kg
Boom Breakout Force	18.5 kN
Bucket Breakout Force	20.4 kN
Dump Clearance at Full Height Discharge	2,220 mm
Dump Reach at Full Height Discharge	540 mm
Maximum Dump Angle at Full Height	40°
Maximum Hinge Pin Height	2,923 mm
Bucket Rollback at Ground Level	30°
Ground Clearance	204 mm
Angle of Departure	26°
Front Clearance Radius with Bucket	1,800 mm

SERVICE CAPACITIES		
Fuel Tank	100 L	
Engine Oil	7 L	
Cooling System	13 L	
Hydraulic Reservoir	52 L	
Hydraulic System Total	70 L	
Chain Tanks, Each	8 L	

OPTIONAL ATTACHMENTS	
4 in 1 Bucket – 0.4 m ³	Auger
Rock Bucket – 0.4 m ³	Snow Blade
Scrap Bucket - 350 to 650 mm	Pick - up Sweeper
Hydraulic Hammer	Hydraulic Shear
Fork	

STANDARD EQUIPMENT	
General Bucket -0.4 m³	8 inch LCD Screen (with bluetooth)
Control Safety Interlock	Radio
Boom Interlock	Flow Standard-76 L/min
Quick Coupler	
Enclosed ROPS/FOPS Cab with AC	
A/C	

OPTIONAL EQUIPMENT	
Solid Tire	Bucket Level Automatically
Tire Chains	Backup Camera
Heater	
Flow High-113 L/min	

